

Time Sensitive Information!

These Configuration Changes Must Be Applied
Ten Days Prior to Norcom Solutions Group
Cut-Over

Cisco RV110(w) EOL, RV130(w) & RV215(w) Router
Configuration For Norcom Solutions Group Cloud Telephony
Deployment
Document Version 2.0

May 15th, 2017

Table of Contents

1. Introduction
2. Firewall Verification Checklist
3. Add Crexendo Services
4. Configure Bandwidth Management

Read Me!

1. These changes must be applied before client implements their Norcom Solutions Group hosted telephony solution.
2. If you are experienced with business class firewalls and routers, please have your IT staff/contractor perform these changes for you.
3. Please read this entire document before attempting to make any changes.
4. If you have questions about this document, you can call 877-667-2661 to schedule an appointment with one of our firewall support specialists. We will attempt schedule your appointment within 24- 48 hours of your call to us so please allow adequate time.
5. After changes are completed please let your client or Norcom Solutions Group Customer Support specialist know.
6. Once completed, a Norcom Solutions Group technician will be requesting access or a collaborative web session to verify settings prior to customer cut over.

Introduction

This document is for IT administrators and illustrates configuration changes required on Cisco RV110/130(w)/215(w) firewall & router appliances to support Norcom Solutions Group's cloud communications telecommunications platform. This document assumes a basic network deployment consisting of one internal LAN network containing the IP phones and one WAN network connected to the Internet. While we strongly recommend a dedicated network for VoIP traffic, the instructions below can be used for a "converged" network whereby both VoIP and non-VoIP traffic share one physical WAN network. With basic modifications (such as adding access rules for additional interfaces); this configuration can be extrapolated for other network layouts. The screenshots below may vary slightly from what is displayed while configuring the device depending on model software version. Setting values not mentioned may be left at default or changed as required for specific purposes.

Please call Norcom Solutions Group Customer Support at 877-667-2661 if you need any further information. Firewall changes can be in depth and you will need to schedule time with one of our specialists if you need assistance.

Firewall Checklist

After applying the GUI configurations in this document, please take the appropriate screen shots to provide the firewall “verification” to Norcom Solutions Group.

Screen Shot #:	Configuration:	Completed:
1	QoS → Bandwidth Management Screen	

Add Crexendo Services

Firewall → Service Management

- Add three services:
 - Crex RTP Ext – UDP 16000 to 17999
 - Crex RTP Int – UDP 11780 to 11800
 - Crex SIP 9000 – TCP&UDP 9000

Small Business
cisco RV215W Wireless-N VPN Firewall

guest (guest) Language: English Log Out About Help

Getting Started
Status
Networking
Wireless
Firewall
Basic Settings
Schedule Management
Service Management
Access Rules
Internet Access Policy
Single Port Forwarding
Port Range Forwarding
Port Range Triggering
VPN
QoS
Administration

Service Management

You must save before you can edit or delete.

Service Name	Protocol	Start Port	End Port
All Traffic	All		
DNS	UDP	53	53
FTP	TCP	21	21
HTTP	TCP	80	80
HTTP Secondary	TCP	8080	8080
HTTPS	TCP	443	443
HTTPS Secondary	TCP	8443	8443
TFTP	UDP	69	69
IMAP	TCP	143	143
NNTP	TCP	119	119
POP3	TCP	110	110
SNMP	UDP	161	161
SMTP	TCP	25	25
TELNET	TCP	23	23
TELNET Secondary	TCP	8023	8023
TELNET SSL	TCP	992	992
Voice(SIP)	TCP & UDP	5060	5061
<input type="checkbox"/> CrexRTPExt	UDP	16000	16999
<input type="checkbox"/> CrexRTPInt	UDP	11780	11800
<input type="checkbox"/> CrexSIP9000	UDP	9000	9000

Add Row Edit Delete

Save Cancel

© 2012 Cisco Systems, Inc. All rights reserved.

Configure Bandwidth Management

QoS → Bandwidth Management

- Click the Bandwidth Management “Enable” check box.
- Enter the contracted WAN upstream and downstream band in Kbit/sec in the “Bandwidth Table.”
- Add each of the following services to the “Bandwidth Priority Table” to accommodate “Upstream” and “Downstream” of each service:
 - Crex RTP Ext
 - Crex RTP Int
 - Crex SIP 9000
 - SIP
- Each service should be added with the following:
 - Upstream and Downstream direction
 - Priority set to High
 - Click to Enable/Yes on **all** services

Bandwidth Management

Setup

Bandwidth Management: ☒ Enable

Bandwidth

The Maximum Bandwidth provided by ISP

Interface	Upstream (Kbit/Sec)	Downstream (Kbit/Sec)
Ethernet	10240	40960
3G	4096	N/A

Bandwidth Priority Table

<input type="checkbox"/>	Enable	Service	Direction	Priority	Interface
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Voice Traffic (Crexendo)[UDP/16000~17999]	Upstream	High	Both (Ethernet & 3G)
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Voice Traffic (Crexendo)[UDP/16000~17999]	Downstream	High	Ethernet
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Voice(SIP)[TCP & UDP/5060~5061]	Upstream	High	Both (Ethernet & 3G)
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Voice(SIP)[TCP & UDP/5060~5061]	Downstream	High	Ethernet
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Voice SIP (Crexendo) for 9000[TCP & UDP/9000~9000]	Upstream	High	Both (Ethernet & 3G)
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Voice SIP (Crexendo) for 9000[TCP & UDP/9000~9000]	Downstream	High	Ethernet
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Crexendo internal port[UDP/11780~11800]	Upstream	High	Both (Ethernet & 3G)
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Crexendo internal port[UDP/11780~11800]	Downstream	High	Ethernet

Buttons: Add Row, Edit, Delete, Service Management

Buttons: Save, Cancel

- Click “Save”

Document Revision History

Version	Reason for Change	Date
1.0 Draft	Initial Draft Document	September 14, 2016
1.1	Firewall Checklist added	March 17 th , 2017
2.0	Revised to include RV215w	May 15 th , 2017